(12) UK Patent Application (19) GB (11) 2 389 064 (13) A

(43) Date of A Publication

03.12.2003

(21) Application No:

0300942.0

(22) Date of Filing:

15.01.2003

(30) Priority Data:

(31) 02030721


(32) 31.05.2002 (33) KR

(71) Applicant(s): Samsung Gwangju Electronics Co Ltd (Incorporated in the Republic of Korea) 271 Oseon-dong, Gwangsan-gu, Gwangju-city, Republic of Korea

- (72) Inventor(s): Jang-keun Oh
- (74) Agent and/or Address for Service: Mathys & Squire 100 Grays Inn Road, LONDON, WC1X 8AL United Kingdom

- (51) INT CL7: B04C 5/22
- (52) UK CL (Edition V): B2P P10B2A2 P5
- (56) Documents Cited: GB 2230474 A EP 0841095 A2 JP 080206543 A US 5275634 A WPI Abstract Accession No 1974-80467 & SU000413960A
- (58) Field of Search: UK CL (Edition V) B2P INT CL7 B04C Other: ONLINE: WPI, JAPIO, EPODOC
- (54) Abstract Title: Self-cleaning mechanism for cyclone overflow grill
- (57) The cyclone-type dust-collecting apparatus for a vacuum cleaner according to the disclosed invention has a grill cleaning means for automatically removing fine dusts covering the grill 30 when the cleaner is in use. The grill cleaning means preferably comprises a grill rotating means (50, fig 3) for rotating the grill while the cleaner is in use and a dusting member 60 disposed to extend along one side of the inner cyclone body (10, fig 1) to contact the outer circumference of the rotating grill. The grill rotating means comprises a rotation member (51, fig 3) disposed at top of the cyclone body to rotatably support the grill in relation to the cyclone body and to rotate together with the grill, connected with the grill by a number of connection members, and having an upper surface of the cyclone body excluding the air discharge port (10b, fig 3) positioned in between, and provided with a gear portion (51b, fig 6) formed around the outer circumference, a driving source for providing driving force for rotating the rotation member, and a power transferring means for transferring power of the driving source to the rotation member via a worm gearing 54, 55. The driving source may comprise a turbine fan 52 disposed in the discharge pipe 12a of the air discharge unit to be rotated by air discharged through the discharge pipe, or may comprise a motor (52a, fig





2 389 064

Self-cleaning mechanism for cyclone overflow grill

Patent number:

GB2389064

Publication date:

2003-12-03

Inventor:

OH JANG-KEUN (KR)

Applicant:

SAMSUNG GWANGJU ELECTRONICS CO (KR)

Classification:

- international:

B04C5/22

- european:

B04C9/00, A47L9/12, A47L9/16, A47L9/20, B01D45/14,

B04C5/13, B04C5/22

Application number: GB20030000942 20030115 **Priority number(s):** KR20020030721 20020531

Also published as:

US2003221278 (A1)

JP2004000408 (A)

FR2840184 (A1)


DE10303678 (A1)

NL1023022C (C2)

more >>

Abstract of GB2389064

The cyclone-type dust-collecting apparatus for a vacuum cleaner according to the disclosed invention has a grill cleaning means for automatically removing fine dusts covering the grill 30 when the cleaner is in use. The grill cleaning means preferably comprises a grill rotating means (50, fig 3) for rotating the grill while the cleaner is in use and a dusting member 60 disposed to extend along one side of the inner cyclone body (10, fig 1) to contact the outer circumference of the rotating grill. The grill rotating means comprises a rotation member (51, fig 3) disposed at top of the cyclone body to rotatably support the grill in relation to the cyclone body and to rotate together with the grill, connected with the grill by a number of connection members, and having an upper surface of the cyclone body excluding the air discharge port (10b, fig 3) positioned in between, and provided with a gear portion (51b, fig 6) formed around the outer circumference, a driving source for providing driving force for rotating the rotation member, and a power transferring means for transferring power of the driving source to the rotation member via a worm gearing 54, 55. The driving source may comprise a turbine fan 52 disposed in the discharge pipe 12a of the air discharge unit to be rotated by air discharged through the discharge pipe, or may comprise a motor (52a, fig 7).



Data supplied from the esp@cenet database - Worldwide